




RUBY-9716VGAR

Intel® Core™ 2 Quad processor based ATX Industrial Mainboard with DDR2 SDRAM, VGA, Gigabit Ethernet, Audio and USB



FEATURES

- Industrial mainboard in ATX form factor supports all Intel® mainstream desktop processors - Core™ 2 Quad, Core™ 2 Duo, Pentium® D, Pentium® 4, Celeron® D processor in LGA-775 package
- Benefits such as Hyper-Threading, EM64T, dual-core, EIST, XD & VT of processor can be easily applied to system by changing processor
- Embedded Intel 4th generation graphics engine provides better user experience of display performance
- One PCI Express x16 slot features high-end graphics card connection interface or dual independent display with ADD2+ media card that provides TV tuner, video capture in and DVI, TV-out
- One PCI Express x4 slot for storage add-in card which provides reliable and safer data storage with adequate I/O throughput
- One PCI Express x1 and four 32-bit PCI expansion slots for most industrial I/O cards
- Five SATA 300 ports together with one IDE channel and CF socket are perfect combination to storage interface for all kinds of applications; supports Intel® Matrix Storage Technology

ORDERING GUIDE

Standard

RUBY-9716VGAR

LGA-775 Core™ 2 Quad processor based ATX Industrial Mainboard with DDR2 SDRAM, VGA, Gigabit Ethernet, Audio and USB

GENERAL

Processor	CPU & Package: Intel® Core™ 2 Quad, Core™ 2 Duo, Pentium® D, Pentium® 4, Celeron® D processor in LGA-775 package FSB: 1066/800/533MHz
Chipset/Core Logic	Intel® Q965 and ICH8DO
System Memory	Up to 8GB DDR2 800/667/533 SDRAM on four 240-pin DIMM sockets
BIOS	Award BIOS
Storage Devices	EIDE: Support single EIDE device with Ultra DMA 100/66/33 SATA: Support five SATA 300 drives
Solid State Disk	One Type II CF socket (only available if no IDE device attached)
Watchdog Timer	Programmable via software from 1 sec. to 255 min.
Expansion Interface	- Four 32-bit PCI expansion slots - One PCI Express x4 slot for x1 or x4 card - One PCI Express x1 slot - One PCI Express x16 slot for PCIe x16 or PCIe x1 or ADD2/+ card
Hardware Monitoring	System monitor (fan, temperature, voltage)
Power Requirement	Typical: +5V@4.0A; +12V@6.5A; 3.3V@3A
Dimension	Dimension : 304.8(L) x 243.8(W) mm; 12"(L) x 9.6" (W)
Environment	Operating Temperature: 0 to 55°C Storage Temperature: -20 to 80°C Relative Humidity: 5% to 90%, non-condensing
MTBF	73,803 hrs

I/O

MIO	Four serial (RS232/TTL selectable x1, RS232/Powered selectable x2, RS232/422/485 selectable x1), one at rear I/O panel, one parallel, one FDD channel
IrDA	IrDA 1.0
Ethernet	- Single 10BASE-T/100BASE-TX/1000BASE-T Ethernet (Intel® 82566DM) - PCI Express x1 interface based Gigabit Ethernet - Single RJ-45 connector with two LED indicators at rear I/O panel
Audio	HDA interface, 2-channel Audio
USB	Eight USB 2.0 ports (Four ports at rear I/O panel; four ports internal)
Keyboard & Mouse	PS/2 keyboard/mouse at rear I/O panel

DISPLAY

Graphic Controller	- GMCH integrated Intel® 4th generation Extreme Graphics controller - Intel® GMA 3000 which provides improved 3D multimedia capabilities including DirectX9, Shader Model 3.0, OpenGL 1.5, Advanced De-interlacing, MPEG-2 hardware acceleration - Support dual independent display with ADD2/+ card
--------------------	--