

Industrial 3.5" 40-pin IDE to 1 PCMCIA PC Card & 1 CF Card Card-drive



Product Feature

- Standard 3.5" drive form-factor
- 1 front CompactFlash type II slot & 1 front PCMCIA type III slot
- ATA to standard 40-pin IDE interface
- 40-pin IDE connector and a 4-pin power Connector
- Hot swappable & bootable
- Support up to UDMA-6 mode
- RoHS & REACH compliant

Specification

Form-factor	Standard 3.5" drive mounted in the front of PC casing
Dimension	109.4mm (L) * 101.6mm (W) * 25.4mm (H)
Weight	G. W.: 230g (W/O Cable)
Host interface	40-pin IDE connector and a 4-pin power connector
Slot Capabilities	1 front slot in CompactFlash type II 1 front slot in PCMCIA type III
Master/Slave Setting	By jumper
Supported Card Type	CompactFlash type I/II and MicroDrive PCMCIA ATA flash card, ATA HDD, and CompactFlash card/ PC card adapter
Power Consumption	5V/75mA typ.
Environmental Specification	
Operating Temperature	0°C ~ 70°C
Non-operating Temperature	-20°C ~ +80°C
Relative Humidity	Max 90%
Hot Swap Function	Yes and software supports DOS, Windows / O.S. No driver needed for Linux
Bootable	Yes and no driver needed
Data Access	PiO mode and DMA mode (up to UDMA-6 mode)
Supported O.S.	Any OS workable per IDE interface
Warranty	1 year